

UNIT - TATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
Robert N. Enfield
3. ADDRESS OF OPERATOR
P.O. Box 2431, Santa Fe, NM 87501
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1650' FS & EL, Sec. 18
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) _____

SUBSEQUENT REPORT OF:

☐
☐
☒
☐
☐
☐
☐
☐

-Amended-Original report showed perforations at 9227'
Corrected to 6227' (NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Recompletion attempt began November 2, 1984 and ended November 13, 1984.

Set Baker CIBP at 7100' with 35' cement on top (7065')

Spotted 200 gallons 10% acetic acid.

Perforated with 1-9/16" tubing gun, 0.28" holes, 1 shot per foot at 6227', 28', 29', 30', 31', 32', 33', 34'.

Swab results showed water with show of gas and oil

Acidized with 2000 gallons 15% NE acid + 16 ball sealers.

Swab recovery showed water with show of gas and oil.

Subsurface Safety Valve: Manu. and Type _____

Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Robert N. Enfield

TITLE Operator

DATE 2/20/85

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE