

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN T
(OTHER INSTRUCTIONS
VERSE SIDE)LOCATE
ORForm approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N. M. 05612-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Marathon Oil Company ✓		8. FARM OR LEASE NAME Federal IBA	
3. ADDRESS OF OPERATOR Box 220 Hobbs, New Mexico		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL and 1650' FWL of Section 15		10. FIELD AND POOL, OR WILDCAT Indian Basin	
14. PERMIT NO. --		15. ELEVATIONS (Show whether DF, RT, GR, etc.) unknown	
		12. COUNTY OR PARISH Eddy	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing test

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Spudded well 7-14-65 and drilled 12-1/4" hole to 182'. Reamed hole to 17-1/2" to 182'. Ran and set 4 joints 13-3/8", 40#, 8R thd., H-40, ST&C, new casing from 11.00' to 177.59'. Last setting depth includes Baker Guide Shoe 1.35'. Casing cemented with 350 sacks Trinity regular cement with 2% calcium chloride and 1/4# Floccale per sack. Cement circulated to surface. WOC 18 hrs and tested casing with 200# for 30 minutes. Tested O.K.

RECEIVED

JUL 23 1965

O. C. C.
ARTESIA, OFFICERECEIVED
JUL 22 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt.

DATE

7-19-65

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

APPROVED

JUL 22 1965

RUDOLPH C. BAUER, JR.
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side