

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR
(Other instruct
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N. M. 051107

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

North Indian Basin Unit

8. FARM OR LEASE NAME

North Indian Basin Unit

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Indian Basin Upper Penn

11. SEC. T. R. M., OR BLK. AND
HURVEY OR AREA

9- 21S - 23E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

Box 220 Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1815' FSL and 1752.3'FEL of Section 9

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

unknown

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Commence drilling & surf. casg

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 12-1/4" hole at 12:05 AM 6-15-65 and drilled to 225'.
Reamed hole to 17-1/2" and ran and set 5 joints 13-3/8", 48#,
H-40, ST&C, new casing from 14.80' below KDB to 223.83'. Setting
depth includes Halliburton guide shoe 1.20'. Casing cemented using
350 sacks Class "A" cement with 2% CaCL and 1/4# Flocele per sack.
Cement circulated. W.O.C. 18 hrs and tested casing with 200# for
30 minutes. Tested O.K. Job completed June 16, 1965.

RECEIVED

JUN 25 1965

ARLINGTON, TEXAS

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt.

(This space for Review of State office use)

APPROVED BY
SIGNATURES OF APPROVAL, IF ANY:

TITLE

R. L. BECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side