

UNITED STATES DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

N. M. O. C. C. COPY
SUBMIT IN T
(Other instruc.
verse side)

ICATE*

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

N. M. 051107

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

7. UNIT AGREEMENT NAME

North Indian Basin Unit

8. FARM OR LEASE NAME

North Indian Basin Unit

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Indian Basin Upper Penn

11. SEC. T. R. M. OR BLK. AND
SURVEY OR AREA

9 - 21S - 23E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

Box 220 Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1815' FSL and 1752.3' FEL of Section 9

14. PERMIT NO.

-

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

unknown

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

casing test

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8-3/4" hole to 7710' TD. Ran and set 222 joints of 23 and 26#, 8R thread, J-55 and C-75, LT&C, new and used casing from 14.00' below KDB to 7709.00'. The last depth includes 1.85' Baker float collar and 1.00 Baker guide shoe. The bottom 700' and from 6300' to 6600' covered w/ Weatherford centralizers and cement baskets set at 7000', 7080' and 7250'. The casing was cemented using 875 sx Trinity Lite Water cement with 12# Gilsomite per sack followed with 200 sacks Incor cement with 11# salt per sack. Cement circulated. W.O.C. 72 hours and tested casing with 2000# for 30 minutes. Tested O.K. Work commenced 7-13-65 and completed 7-16-65.

RECEIVED

JUL 22 1965

O. C. C.
ARTESIA, N. M.

RECEIVED
JUL 23 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt.

DATE

7-19-65

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JUL 21 1965
RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side