

Form 9-331
(May 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. 0251099
2. NAME OF OPERATOR Pan American Petroleum Corp.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 68 Hobbs N.M. 88240		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' FNLX 1650' FWL Sec 11 (Unit F, SE 1/4 NW 1/4)		8. FARM OR LEASE NAME J. H. SMITH
14. PERMIT NO.		9. WELL NO. 1
15. ELEVATIONS (Show whether DF, RT, GR, etc.)		10. FIELD AND POOL OR WILDCAT INDIAN BASIN (UPPER)
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 11-22-23 N.M.P.M.
		12. COUNTY OR PARISH EDDY
		13. STATE N.M.

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Lowe Drilling Co. Midland, Texas spudded
17 1/2" hole at 4:30 A.M. on 5-6-65. On 5-9-65,
13 3/8" OD 48" - 54.5" H-40 + J-55 ST# C Casing
was set at 200' w/ 150 sx. Incon + 1/2" of
Flo Seal + 2% Calc. + 150sx. Incon + 2% Calc.
Cement Circ. After 18 hours, tested
Casing w/ 800 psi for 30 minutes. Test
O.K. Reduced hole to 11" at 200'
and resumed drilling operations.

RECEIVED

MAY 14 1965

N. M. O. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED

Original Signed By
C. R. WILLIAMS, JR.

TITLE

Area Foreman

DATE

5-10-65

(This space for Federal or State office use)

APPROVED
CONDITIONS OF APPROVAL, IF ANY.

TITLE

DATE

MAY 12 1965
RUDOLPH C. BAUER, JR.
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

0+7

0+4- USGS
c- JWB
c- Susp
c- WIS

RECEIVED
MAY 12 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO