

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. MM 045272
2. NAME OF OPERATOR Standard Oil Company of Texas A Division of Chevron Oil Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 3610 Avenue B - Snyder, Texas		7. UNIT AGREEMENT NAME Eagle Flats Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface Unit G, 1630' FWL and 1650' FWL of Section 8, T-22-S, R-23-E		8. FARM OR LEASE NAME Eagle Flats Unit
14. PERMIT NO.		9. WELL NO. 6
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GR 4214		10. FIELD AND POOL, OR WILDCAT Indian Basin, Upper Permian, Upper G
		11. SEC., T., R., M., OR BLM. AND SURVEY OR AREA Sec. 8, T-22S, R-23E
		12. COUNTY OR PARISH Hddy
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) **Supplementary Well History**
(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded well 1:15 A.M. 9-14-65, drilled 17 1/2" hole to 265'. Ran new 13-3/8" 48# J-55 casing to 264' and cemented to surface with 250 sms. cement. WOC 2:15 P.M. 9-15-65 after WOC 18 hours tested casing at 1000 psi, no pressure loss in 30 mins.

Drilled ahead in 12 1/2" hole to 2300', landed new 9-5/8" 36# J-55 casing at 2300'. Cemented to surface with 700 sms cement. WOC 3:30 A.M. 9-22-65. After WOC 18 hours tested casing at 1000 psi, no pressure loss in 30 mins.

Drilling ahead in 8-1/4" hole to present depth of 6915'.

RECEIVED
OCT 11 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED


TITLE **Lead Drilling Engineer**

DATE **October 6, 1965**

(This space for Federal or State office use)

TITLE

DATE



*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.