m 3160-5 LINIT		°евіа, № 88210
DEPARTMENT	ED STATES OF THE INTERIOR	FORM APPROVED Budget Bureau No. 1004–0135
BUREAU OF LA	ND MANAGEMENT	Expires: Merch 31, 1993
SUNDRY NOTICES AND	REPORTS ON WELLS	5. Lesse Designation and Serial No. NM 045272
o not use this form for proposals to drill or de		6. If Indian, Allottee or Tribe Name
	OR PERMIT-" for such proposals	N/A
ype of well Oli Oli Control Ol	RECEIVED	7. If Unit or CA, Agreement Designation N/A 8. Well Name and No.
lame of Operator	1	Bogle Flats Unit No. 6
EVRON U.S.A. PRODUCTION CO. , INC.	MAY 0.9. '04	9. API Well No.
Address and Telephone No.	<u> </u>	30-015-10578
	(915) 687-7182 O. C. D	10. Field and Pool, or Exploratory Area
ocation of Well (Footage, Sec., T., R., M., or Survey Descripti	on) ARTESIA, OFFICE	Indian Basin
Section 8, T22S - R23E		11. County or Parish, State
1,650' FNL - 1,650' FEL Unit G		Eddy County, NM
	(S) TO INDICATE NATURE OF NOTICE, REF	
TYPE OF SUBMISSION	TYPE OF ACTION	ONT, ON OTHER DATA
X Notice of Intent	Abendonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Beck	Non-Routine Frecturing
	Casing Repair	Water Shut-Off
Finel Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Gas Glycol Dehydration	Dispose Water
maintaining a lower moisture content in The packaged unit will be mounted on a	to adequately protect the bare carbon steel the gas stream due to the recent production structural steel skid and will be set on a pol	n increases.
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis colors before installation on the location.	urrounding soil. This pad will be surrounded conmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved
to prevent glycol contamination of the su to contain fluid leaks and minimize enviro and will not require additional surface dis colors before installation on the location.	urrounding soil. This pad will be surrounded onmental damage. It will be located on the sturbance. The equipment will also be paint	by an earthen dike existing well site red with BLM approved