

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN THE
(Other instruct. on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.
IN 4881

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER		7. UNIT AGREEMENT NAME Logle Flats Unit
2. NAME OF OPERATOR Standard Oil Company of Texas		8. FARM OR LEASE NAME Logle Flats Unit
3. ADDRESS OF OPERATOR A Division of Chevron Oil Company		9. WELL NO. 7
3610 Avenue S - Snyder, Texas		10. FIELD AND POOL OR WILDCAT Indian Basin, Upper Perm. Gas
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface Unit J: 1650' FSL and 1650' FSL of Section 7, T-22S, R-23E		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 7, T-22S, R-23E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) Gr. 4197.3	
12. COUNTY OR PARISH Eddy		13. STATE N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Run drill pipe open ended, set cement plugs as follows per 1500 requirements:

7850-8057' with 65 sms cement.
7400-7550' 35 "
6000-6100' 30 "
4400-4500' 30 "
3250-3350' 30 "
1900-2050' 50 "
400- 500' 30 "

Released rig at 4:00 P.M. 11-12-65, removed well head equipment, set 10 sack cement plug in top of 9-5/8" casing, welded steel plate with needle valve on 13-1/8" casing. Cleaned up location, installed abandoned well marker 11-20-65.

RECEIVED
NOV 26 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED

FEB 4 1966

F. L. B. J.
ACTING DISTRICT ENGINEER

18. I hereby certify that the foregoing is true and correct

SIGNED *G. Davidson* **G. Davidson**

TITLE **Lead Drilling Engineer** DATE **November 23, 1965**

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

*See Instructions on Reverse Side

APPROVED
FEB 3
F. L. B. J.
ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE : 1963-O-685229

867-851