

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN ()
(Other instr. is on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

New Mexico 03699

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	AUG 30 1965		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR John H. Trigg	O. C. C. ARTESIA, OFFICE		8. FARM OR LEASE NAME Federal "18"
3. ADDRESS OF OPERATOR Post Office Box 106 - Maljamar, New Mexico			9. WELL NO. 2
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650 Feet from North Line and 1650 Feet from West Line			10. FIELD AND POOL, OR WILDCAT Indian Basin
14. PERMIT NO.	15. ELEVATIONS (Show whether BF, RT, GR, etc.) 4021.4 hbm	11. SEC., T., R., M., OR HLM. AND SURVEY OR AREA S. 7, T22S, R24E, N47W	
		12. COUNTY OR PARISH Idaho	13. STATE N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) Running surface casing	XX

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was spudded at 1:30 a.m. August 23, 1965. At a total depth of 200' on August 24, 1965, we ran 193.55' of 13-3/8" OD .290" wall 35.64 slip joint casing. Casing was set at 200' and cemented with 230 sacks Incoer Poccin w/2% gel and 2% CaCl₂. Cement circulated with 23 sacks excess. Pumped plug down @ 11:30 a.m. August 24, 1965.

Waited on cement 12 hours, went in hole and pressure tested @ 300 psi for 30 minutes. Hold ok. Blow hole dry and drilled out with air.

Drilling ahead.

18. I hereby certify that the foregoing is true and correct

SIGNED Kenneth E. Astor TITLE Production Clerk DATE August 26, 1965

(This space for Federal or State office use)

APPROVED
AUG 27 1965
RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
AUG 27 1965
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

