(Do not use this form	GEOLOGICAL S NOTICES AND RE for proposals to drill or to dec "APPLICATION FOR PERMIT-	PORTS ON	N WELLS		NM-0468129 IF INDIAN, ALLOTTEE OR TH	IBE NAT
1	'APPLICATION FOR PERMIT	'' for such prop	03 ais.)	7.	UNIT AGREEMENT NAME	
OIL GAS WELL X	OTHER				FARM OR LEASE NAME	
2. NAME OF OPERATOR Humble Oil & Refining Company				Willow Draw Unit		
3. ADDRESS OF OPERATOR					WELL NO.	
Box 210C, Hobbs, New Mexico 8824C 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*			10]. FIELD AND FOOL, OR WILL	CAT	
See also space 17 below.) At surface 2106 FNL, 1830 FEL, Sec. 30, T-20-S, R-26-E, Eddy County,					EVEN RIVERS Hill BEC., T., B., M., OR BLK. AN SUBVEY OR AREA	
New Mexico.				Se	c. 30. T-20-S.	R -26
14. PERMIT NO.	15. ELEVATIONS (SI			12.	COUNTY OF PARISH 13.	
***	To be fur	nished at	a later date.		Eddy New	Mex
16. C	heck Appropriate Box To	o Indicate Nat	ture of Notice, Repor	t, or Othe	r Data	
NOTIC	OF INTENTION TO:			SUBSEQUENT	REPORT OF:	
TEST WATER SHUT-OFF	PULL OR ALTER CASIN	NG	WATER SHUT-OFF		REFAIRING WELL	
FRACTURE TREAT	MULTIPLE COMPLETE		FRACTURE TREATMEN Shooting or acidizi		ALTERING CASING ABANDONMENT*	
SHOOT OR ACIDIZE	ABANDON*		(Other)	······································		
REPAIR WELL	CHANGE PLANS					.11
Spudded 17 ¹ / ₂ " hol 48#, H-40, set a	LETED OPERATIONS (Clearly statis directionally drilled, give s e at 10:00 PM, 10- t 350'. Cemented	-13-65. Ra with 250 s	Completion or details, and give pertinen as and measured and tru an 326! (10 joi sxs Incor 4% Ge	nts) 13-	-3/8" casing, 7:15 AM,	tarting
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet pressure for 30 m	-13-65. Ra with 250 side of cas nent at 60 eted at 2:2	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COND proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet pressure for 30 m	-13-65. Ra with 250 side of cas nent at 60 eted at 2:2	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet pressure for 30 m	-13-65. Ra with 250 side of cas nent at 60 sted at 2:4 ninutes - 1	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet pressure for 30 m	-13-65. Ra with 250 side of cas nent at 60 sted at 2:4 ninutes - 1	Completion or details, and give pertinen an 326' (10 joi: sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet pressure for 30 m	-13-65. Rawith 250 side of cashed at 2: ninutes - 1 $\kappa \in \mathbb{C}$	Completion or details, and give pertinen an 326' (10 joi: sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet f pressure for 30 m	-13-65. Rawith 250 side of cashed at 2: ninutes - 1 $\kappa \in \mathbb{C}$	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet f pressure for 30 m	-13-65. Rawith 250 side of can nent at 60 eted at 2: ninutes - r r t C C	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COM proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s t 350'. Cemented tobe tubing on outs each. Top of cen urface. Job complet f pressure for 30 m	-13-65. Rawith 250 side of can nent at 60 eted at 2: ninutes - r r t C C	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres	nts) 13- in two l. POB in two O sxs Ir . WOC]	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COll proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600#	e at 10:00 PM, 10- is directionally drilled, give s to 350'. Cemented tobe tubing on outs each. Top of cem arface. Job complet f pressure for 30 m of. Drilling.	-13-65. Ra with 250 side of can nent at 60 eted at 2: ninutes - 1 k E C E OCT 2	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres IVED 8 1975	Recompletion it dates, incle e vertical de 1. POB in two 0 sxs In . WOC 1 .sure. I	-3/8" casing, 7:15 AM, stages of 100 ncor and 18 hours. Teste Drilled plug at	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COM proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Cel circulated to su casing with 600# 8:30 AM, 10-16-6 18. I hereby certify that the SIGNED	e at 10:00 PM, 10- is directionally drilled, give s at 350'. Cemented tobe tubing on outs each. Top of cemer foressure for 30 m of. Drilling.	-13-65. Ra with 250 side of ca nent at 60 eted at 2: ninutes - 1 K E E E OCT 2	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres	Recompletion it dates, incle e vertical de 1. POB in two 0 sxs In . WOC 1 .sure. I	-3/8" casing, 7:15 AM, stages of 100 acor and 18 hours. Teste	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COM proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Gel circulated to su casing with 600# 8:30 AM, 10-16-6 18. I hereby certify that the SIGNED	e at 10:00 PM, 10- is directionally drilled, give s at 350'. Cemented tobe tubing on outs each. Top of cemer foressure for 30 m of. Drilling.	-13-65. Ra with 250 side of cas nent at 60 eted at 2:7 ninutes - 1 N E E E OCT 2 ARTE	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres IVED 8 1975	Recompletion it dates, incle e vertical de 1. POB in two 0 sxs In . WOC 1 .sure. I	-3/8" casing, 7:15 AM, stages of 100 ncor and 18 hours. Teste Drilled plug at	tarting zones p
(Other) 17. DESCRIBE PROPOSED OR COM proposed work. If well nent to this work.)* Spudded 17½" hol 48#, H-40, set a 10-15-65. Ran H sxs Incor 4% Cel circulated to su casing with 600# 8:30 AM, 10-16-6 18. I hereby certify that the SIGNED	e at 10:00 PM, 10- is directionally drilled, give s at 350'. Cemented tobe tubing on outs each. Top of cemer foressure for 30 m of. Drilling.	-13-65. Ra with 250 side of can nent at 60 eted at 2: ninutes - 1 k E C E OCT 2	Completion or details, and give pertinen an 326' (10 join sxs Incor 4% Ge sing and pumped '. Pumped in 3 45 PM, 10-15-65 no drop in pres IVED 8 1975	Recompletion it dates, incle e vertical de 1. POB in two 0 sxs In . WOC 1 .sure. I	-3/8" casing, 7:15 AM, stages of 100 ncor and 18 hours. Teste Drilled plug at	tarting zones p

•

۰.

.

•

,

.