

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Blanket Bureau No. 1001-0115
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 35361

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

RECEIVED

1. NAME OF OPERATOR

National Coop. Refinery Assoc.

2. ADDRESS OF OPERATOR

415 W. Wall, Suite 2215, Midland, Texas 79701

3. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)

See also space 17 below.
At surface

2106' FNL & 1830' FEL

14. PERMIT NO.

-

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3427' DF

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Willow Draw Unit

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Seven Rivers Hills (W/C)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T-20-S, R-26-E

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐

PULL OR ALTER CASING

☐

FRACTURE TREAT

☐

MULTIPLE COMPLETE

☐

SHOOT OR ACIDIZE

☐

ABANDON*

☐

REPAIR WELL

☐

CHANGE PLANS

☐

(Other)

☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐

REPAIRING WELL

☐

FRACTURE TREATMENT

☐

ALTERING CASING

☐

SHOOTING OR ACIDIZING

☐

ABANDONMENT*

☐

(Other) Re-Entry

Re-Entry

☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

Re-Entry Procedure:

CONFIDENTIAL REPORT

Drill out Plug #1 from Surface to 18'. (Length - 18')
Drill out Plug #2 from 2528' to 2703'. (Length - 175')
Drill out Plug #3 from 3706' to 3968'. (Length - 262')
Drill out Plug #4 from 5483' to 5640'. (Length - 157')
Drill out Plug #5 from 7270' to 7386'. (Length - 116')
Drill into Plug #6 from 7490' to 7567'. Circulate to surface.

Ran Gamma Ray & Caliper Logs from 7500' to bottom of 8 5/8" casing @ 2344'.

DST #1: Unsuccessful due to packer seat failure.

DST #2: IF 5" 37-43 psi/ISI 43" 911 psi/
FF 119" 51-81 psi/FSI 357" 1403 psi.
Gas to surface 1 1/2 hrs./Rec 240' GCM/SC Rec 0.4 SCF Gas.

18. I hereby certify that the foregoing is true and correct

SIGNED Carrie A. Baze

TITLE Production Clerk

DATE 10-19-88

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY Carrie A. Baze

TITLE Production Clerk

DATE 10-19-88

CONDITIONS OF APPROVAL, IF ANY:

OCT 28 1988

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO