

orm 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OIL CONSERVATION DIV
811 S. 1st ST.
Albuquerque, NM 88210-2834

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

C/SF

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.
NM-NM86891 and NM-NM95629
6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Nearburg Producing Company

3. Address and Telephone No.

P.O. Box 823085, Dallas, TX 75382-3085 214/739-1778

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

2,106' FNL and 1,830' FEL, Section 30, T20S; R26E

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Willow Draw #1

9. API Well No.

10. Field and Pool, or Exploratory Area

Wildcat Cisco Canyon

11. County or Parish, State

Eddy County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Production Casing and Cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Finish drilling out cement from 8,380' to 8,562'. C&C hole. POH and LD DP and DC's. RU and run 229 jts 5-1/2" 17# and 20#, K-55 and N-80 LT&C csg to 8,562'. C&C hole. Cement csg using 550 sx cement. Theoretical TOC at 6,500'. ND BOPE and set slips in 120,000# tension. Cut-off csg and NU tbg head.

RECEIVED
JUN 20 1996
C.R. Kimbrough
6/20/96

[Signature]

14. I hereby certify that the foregoing is true and correct

Signed C.R. Kimbrough

Title Mgr Drilling and Production

Date 6/07/96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

*See Instruction on Reverse Side