

N. M. O. C. G. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN 1. LOCATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NE 002535

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 28

9. WELL NO.

1

10. FIELD AND POOL OR WILDCAT

**Indian Wells - 1st
Pumpjack No. 1**

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

28-212-031

12. COUNTY OR PARISH 13. STATE

El Paso

New Mexico

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Union Oil Company of California

3. ADDRESS OF OPERATOR

619 West Tenth Avenue, Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

SW 1/4 NE 1/4, 1980' FNL & 1980' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3936.5' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded at 12:05 a.m., 10-28-65 and drilled 15" hole to 248'.

Ran & cemented 231.18', 13-3/8", 48#, used casing at 247' with 100 cu. linear cement with 33 cu. ft. Strata Crete, 25 gal and 25 calcium Chloride added, followed by 150 cu. reg. 4 1/2 gal cement with 25 calcium chloride. Cement circulated.

C.I.P. at 9:45 a.m., 10-29-65. Waited on cement 18 hours. Tested casing with 1000# for 30 minutes. OK.

Drilled 11" hole to 2202'.

Ran & cemented 2185.07' 8-5/8", 24#, new casing at 2202' with total of 1675 cu. cement. Cement circulated. C.I.P. at 4:45 a.m., 11-3-65.

Waited on cement 18 hours. Tested casing with 1500# for 30 minutes. OK.

RECEIVED

NOV 9 1965

RECEIVED

NOV 8 1965

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. J. Dyer

TITLE

Production Clerk

DATE

November 5, 1965

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
Rudolph C. Dyer, Jr.
RUDOLPH C. DYER, JR.
ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.