

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN 7 LICATION
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0349880

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Salt Canyon Unit

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC. T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 6-22S-25E NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☐ OTHER ☒ Drilling

2. NAME OF OPERATOR

The Atlantic Refining Company

3. ADDRESS OF OPERATOR

P. O. Box 1978, Roswell, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

720' FNL & 790' FNL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3758' DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☒CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well was drilled to a total depth of 8041'. Mud logger, electric logs & a drill stem test proved the well to be non-commercial. we propose to plug the well by setting the following Incor cement plugs. 9#/gal. mud will be used to spot plugs.

1. 35 sx from 7940 - T.D.

2. 35 sx from 7160-7260

3. 35 sx from 5690-5790

4. 35 sx from 2960-3060

5. 35 sx from 2440-2540

6. 105 sx from 1165-1465

7. 35 sx from ground level to 125'

13-3/8" & 8-5/8" casing strings will remain intact. Dry hole marker will be installed and location cleared in accordance with USGS requirements.

Above program approved by Mr. Knauf on 3-31-66.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Dist. Drilling Supervisor

DATE

4-14-66

(This space for Federal or State office use)

APPROVED IN CONNECTIONS OF APPROVAL, IF ANY:

TITLE

DATE

RECEIVED
APR 15 1966
U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals for abandonment of a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement, or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of setting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking for approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229

947-681

