

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN THE MANNER INDICATED  
(Other instructions on reverse side)Form approved/  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0384625

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal IBC Gas "Com"

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Indian Basin upper Pennsylv

11. SEC. T., R., M., OR BLK. AND SURVEY OR AREA

29-21S-23E

12. COUNTY OR PARISH

13. STATE

D. C. C. Eddy

N. M.

SUNDRY NOTICES AND REPORTS ON WELLS  
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Marathon Oil Company

3. ADDRESS OF OPERATOR

Box 220 Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)  
At surface

1700' FSL and 1550' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

unknown

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Casing test

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Well was drilled to 2039', 11" hole, April 12, 1966. Ran and set 65 jts 8-5/8", 32#, 8R thd., J-55, ST&C Cond. 1 casing from 18.20' below KD to 2037.00'. Last depth includes Baker Circ. Flex Flo collar 1.55' and Baker Guide Shoe 1.13'. Casing cemented with a total of 1550 sacks (1250 sx Trinity Lite Wate; 100 sx Class A with 2% calcium chloride; 50 sx w/ 3% calcium chloride; 150 sx w/ 4% calcium chloride) cement in 5 stages. Cement circulated to surface. WOC 18 hours and tested with 2000# for 30 minutes, holding O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Area Supt.

DATE

4-15-66

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL IF ANY:

APPROVED  
RUBEN C. BAIN, JR.  
ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side