

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 03677

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

Stebbins Deep Fed.

8. FARM OR LEASE NAME

WELL NO.

Wildcat

10. FIELD AND POOL, OR WILDCAT

30-20S-29E

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Harvey E. Yates

3. ADDRESS OF OPERATOR

305 Carper Bldg., Artesia, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980 fr N and 990 fr E, 30-20S-29E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3236 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Running of 7" casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

We ran 290 jts. 12,195' of 7" csg. With a float shoe and float collar on bottom jt. with 15 centralizers, one on every other collar for 30 jts. We also ran a Halliburton D. V. Packer collar set at 10936', a Halliburton D. V. Mult. - Stage Cementer set at 4486' with 2 Halliburton Cement Baskets placed at 4528' and 4570'.

STAGE #1 - Cemented via shoe with 350 sacks of Type C - containing 2% Gel, 1.25% CFR-2 and 8# Salt Per Sack.

STAGE #2 - Cemented via Halliburton D. V. Packer Collar with 500 sacks of trinity Lite Water-containing 8# Salt Per Sack.

STAGE #3 - Cemented Via Halliburton D. V. Multi-Stage Cementer with 500 sacks of 50-50 Pozmix A - Type C with 10# Salt Per Sack.

Total of 1350 Sacks.

NOTE - Casing in hole-

#1 in hole 26 Jts	1055'	29#	P110
#2 in hole 68 Jts	2818'	29#	N80
#3 in hole 61 Jts	2614'	26#	N80
#4 in hole 68 Jts	2912'	23#	N80
#5 in hole 67 Jts	2782'	23#	N80 Buttress

CONFIDENTIAL

18. I hereby certify that the foregoing is true and correct

Plus float shoe, float collar & D. V. Tools.

SIGNED

TITLE Bookkeeper

DATE July 11, 1966

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

APPROVED

JUL 11 1966

RUDOLPH C. BAUER, JR.
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side