

DRILL STEM TESTS

HARVEY E. YATES STEBBINS FED. DEEP NO. 1

DST - 3222-3260 - Tool open 135", no gas to surface
Rec. - 1682' gas in drill pipe, 130' free oil (Gr. 41 deg)
633' of oil and gas cut water.
60" - ISIP 1432 45" FSIP 1445
IFP 131 FFP 255

DST - 8426-8720 - Tool open 126", GTS 45", TSTM
Rec. - 170' Drilling fluid.
60" - ISIP 605 120" 590
IFP 180 FFP 225

DST - 9378-9495 - Tool open 245" GTS 4", 49, 175 CFGPD
Rec. - 295' oil, 695' oil and gas cut drilling fluid.
60" - ISIP 3820 120" FSIP 3739
IFP 430 FFP 449

DST - 10380-10525 - Tool open 125", no gas to surface
Rec. - 371' Drilling fluid
120" - ISIP 4410 160" FSIP 3396
IFP 162 FFP 311

DST - 10496-10685 - Tool open 305", GTS 58", TSTM
Rec. - 161' Drilling fluid
150" ISIP 1159 240" FSIP 2959
IFP 193 FFP 371

DST - 10736-10885. Tool open 96", GTS 11", TSTM
Rec. - 90' Drilling fluid
150" ISIP 1114 150" FSIP 1215
IFP 135 FFP 129

DST - 11266-11280 - Tool open 185", GTS 14", TSTM
Rec. - 15' Drilling fluid
120" - ISIP 3563 150" FSIP 4148
IFP 60 FFP 43

DST - 11275-11405. Tool open 245", GTS 3", 4400 MCFGPD
Rec. - 30' of 51 deg. distillate, 28' drilling fluid
150" - ISIP 5012 240" FSIP 4900
IFP 1275 FFP 1587

DST - 11470-11521 - Tool open 82", no gas to surface
Rec. - 203 of drilling fluid
180" - ISIP 798 90" FSIP 1473
IFP 92 FFP 165

DST - 11643-11694 - Tool open 67", no gas to surface
Rec. - 125' of drilling fluid
180" - ISIP 4781 90" FSIP 4380
IFP 60 FFP 90

DST - 13141-13157 - Tool open 45", no gas to surface
Rec. - 95' drilling fluid, 115' dark, sl oil cut water
90" ISIP 5720 60" FSIP 5725
IFP 60 FFP 133