

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

NM OIL CONS COMMISSION
Drawer DD
Artesia, NM 88210

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir
Use "APPLICATION FOR PERMIT--" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvey E. Yates Company

3. Address and Telephone No.

P.O. Box 1993, Roswell, NM 88202 1-505 623-6601

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UNIT LETTER H, 1980' FNL & 990 FEL
SEC. 30, T-20S, R-29E

5. Lease Designation and Serial No.

NM-03677

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

STEBBINS DEEP FED. #1

9. API Well No.

30-015-10794

10. Field and Pool, or Exploratory Area

SCANLAN DELAWARE

11. County or Parish, State

EDDY CO., NM.

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

TYPE OF ACTION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other P&A

☐ Change in Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

CALLED BLM BY MAYO MARRS ON 5-4-95 AND BY HEYCO ON 5-5-95

P&A ACTIVITY

OPEN PERFS: 3238-40' & 3339-41.5' (DELAWARE)

- 5-5-95 MI & RU MAYO MARRS. RUN 292 JTS IN HOLE TO 9190'.
- PUMPED 45 SK PLUG CL C (150' PLUG (TOP OF WOLFCAMP) 9190-9040')
- PUMPED GEL AND 35 SK PLUG (100' PLUG (TOP OF BONE SPRING) 5790-5690')
- PUMPED GEL AND 65 SK PLUG (350' PLUG +/- FROM 3400-3070' (ACROSS DELAWARE PERFS & INTERM. SHOE. @ 3170'. WOC & TAGGED AT 3038'.
- PUMPED GEL AND 25 SK PLUG (100' PLUG FROM 770' TO 670' (SURFACE SHOE))
- CIRC 15 SK PLUG TO SURFACE (50' SURFACE PLUG) & INSTALLED DRYHOLE MARKER.
P&A COMPLETED 5-9-95.
- PIT BACKFILLED AND MATERIALS LEFT ON LOCATION FOR ALLOCATION TO PARTNERS.
ONCE ALLOCATION AND BIDS ARE IN AND ACCEPTED THEN MATERIALS WILL BE REMOVED AND LOCATION WILL BE RECLAIMED

14. I hereby certify that the foregoing is true and correct

Signed

RAY F. NOKES

Title

PROD. MGR./ ENG.

Date 5/12/95

(This space for Federal or State office use)

Approved by

C/O, Signed by: [Signature]

Title

Date 6/27/95

Conditions of approval, if any: