

S. J. JORDINS DEEP FEDERAL NO. 1
 SECTION 30-20-29, EDDY CO., TEXAS
 Delaware Production and Downhole Injection Assembly

11,296' N80 Tbg

12,195' N80 Csg

Note: The long string is design to flow either zone, selectivity

Shut
AV Drill rig 600 BPD

AV latr 500 - 600 BPD

Closed system

Analysis 550 # for 500

Grant minimum

SBT2' survey this well

3302' J-55 Tbg

Delaware Perf
 2 shots per ft
 3238-3240'
 3239-3241.5'

← Otis RDH Dual (12 RDH 7007) Hydraulic Packer

Set → 3190'

2 3/8" Seating Nipple

DUG 4486 - Cont. Casing to Surface?
See 4x 50 - 50 PDS

2 3/8 600

Plastic lined

← Otis J slot seal w/OS tubing seal divider w/N Nipple

10,476'

← Otis WA Permanent (212 WA 7008) 3 1/2" Bore Packer

Have completion tests been run?

Strawn Perf
 2 shots per ft

10,501'-10,577'

← Perforated Sub

← Otis 121 x A 3 SS D sliding side door

11,250'

← Otis WA Permanent (212 WA 7008) 3 1/2" Bore Packer w/10' seal assm in place
 1 1/2" Otis "N" Nipple w/1 1/2" Mule shoe below

Morrow Perf

11,276'-11,333'
 11,401'-11,411'