

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT 1. DUPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-21424.
5. LEASE DESIGNATION AND SERIAL NO.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR <i>Humble Oil & Refining Company</i>		8. FARM OR LEASE NAME <i>North Ocho, 110-Unit</i>
3. ADDRESS OF OPERATOR <i>Box 1600, Midland, Texas 79701</i>		9. WELL NO. <i>1</i>
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface <i>3060 FNL, 1993 FEL, 7 Sec. 5, T-21-S, R-27-E, Eddy County, New Mexico.</i>		10. FIELD AND POOL, OR WILDCAT <i>Wildcat</i>
14. PERMIT NO. <i>—</i>		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA <i>Sec. 5, T-21-S, R-27-E</i>
15. ELEVATIONS (Show whether DF, RT, GR, etc.) <i>3296 DF</i>		12. COUNTY OR PARISH <i>Eddy</i>
		13. STATE <i>New Mexico</i>

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recombination Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Well plugged. The following plugs were set:

- Plug #1 from 11,629 - 11,530 with 40 cps slo-set cement.
 Plug #2 from 11,000 - 10,900 with 40 cps slo-set cement.
 Plug #3 from 10,700 - 10,400 with 100 cps slo-set neat cement.
 Plug #4 from 10,250 - 10,150 with 40 cps slo-set neat cement.
 Plug #5 from 8,570 - 8,470 with 40 cps slo-set neat cement.
 Plug #6 from 6,500 - 6,400 with 40 cps slo-set neat cement.
 Plug #7 from 5,000 - 4,900 with 40 cps slo-set neat cement.
 Plug #8 from 3,200 - 3,700 with 40 cps slo-set neat cement.
 Plug #9 from 2,630 - 2,500 with 70 cps slo-set neat cement.

Mud laden fluid between plugs. Casing head salvaged. Wellhead on 8 5/8" nipple for U. S. G. S. Well turned over to U. S. G. S. for water observation tests.

18. I hereby certify that the foregoing is true and correct

SIGNED

H. L. Clemmer

TITLE

Agent

DATE

8-4-66

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
 JUL 13 1967
 R. L. BECKWITH
 ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side