

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN
(Other Instr
verse side)PLICATE
as of reForm approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ DRY HOLE	7. UNIT AGREEMENT NAME BIG EDDY UNIT FEDERAL
2. NAME OF OPERATOR PAN AMERICAN PETROLEUM CORPORATION	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR BOX 68, HOBBS, N. M. 88240	9. WELL NO. 16
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL x 1980' FEL, Sec. 18 (Unit J, NW 1/4 SE 1/4)	10. FIELD AND POOL, OR WILDCAT WILDCAT
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 18-21-29 NMPM
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3309' R.D.B.	12. COUNTY OR PARISH EDDY
	13. STATE N.M.

RECEIVED

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
☐ TEST WATER SHUT-OFF	☐ PULL OR ALTER CASING	☐ WATER SHUT-OFF	☐ REPAIRING WELL
☐ FRACTURE TREATMENT	☐ MULTIPLE COMPLETE	☒ FRACTURE TREATMENT	☐ ALTERING CASING
☐ SHOOT OR ACIDIZE	☐ ABANDON*	☐ SHOOTING OR ACIDIZING	☐ ABANDONMENT*
☐ REPAIR WELL	☒ CHANGE PLANS	(Other)	
(Other)		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD-12977. PBD12120; 4 1/2" OD 11.6-13.5' J-55 + N 80 Casing was set @ 12 720' w/ 650 sq. Trinity Inferno. Tested w/ 3100 psi for 30 minutes. Test OK. Perforated Morrow 12448-68, 12516-24, 12548-76, 12600-640 w/ 2JSPF. Acidized w/ 2000 gal MCA + 20,000 gal 15%. Evaluated. Perforated Atoka 11573-81' w/ 2JSPF. Evaluated. On 12-30-66 Zones flowed at rate of 650 MCFGPD. Non-Commercial.

Pursuant to telephone approval of 1-3-67, Messrs Beekman to Smith, propose to P&A as follows: Load hole w/ mud. Spot 20 sq plug 11,600-450; Shoot + pull 4 1/2" Csg from free point - approx 11:400; Spot 45 sq cement plug in + out of 4 1/2" stub. 45 sq plugs at intervals, 10150-050, 8600-8500; 7650-7550, 6500-6400; 5100-5000; in & out of 9 5/8" Csg shoe set @ 3016. Spot 10 sq at surface + erect P&A marker. Make final cleanup and restore ground to contour.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

AREA SUPERINTENDENT

DATE

1-4-66

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL:

TITLE

DATE

APPROVED
JAN 10 1966
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

2-4- USGS-ART
1- NSW
1- SUSP
1- RRY
1- PERRY R BASS
1- STATE LAND
1- NMOCCL 54