

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form Approved,
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0338758

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

RECEIVED

FEB 5 1975

B. C. C.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

Springs Unit Federal

8. FARM OR LEASE NAME

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Springs Upper Penn.

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 34, 20-S, 26-E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, OR, etc.)

3221' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Plugged and Abandoned

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8800' TD.

Pulled production equipment. Ran CI BP and set at 7935', above Baker Model D packer at 7950'. Loaded hole with 10.0# brine containing 25 sacks of Zeogel per 100 barrels of brine. Ran free point and cut and recovered 5-1/2" casing from 6708'. Spotted 20 sack cement plug from 6758' to 6558', across 5-1/2" casing stub at 6708'; 29 sack cement plug from 5050' to 4950', across top of Bone Springs sand at 5020'; 30 sack cement plug from 2764' to 2664', across 8-5/8" shoe at 2714' and 15 sack cement plug from 50' to surface. Installed dry hole marker. Plugged and abandoned December 26, 1974. Will advise when location is ready for inspection.

RECEIVED

DEC 27 1974

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W. B. Borland

TITLE

Area Production Manager

DATE

December 26, 1974

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

*passed
at a
2-2-75*