

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

JUL 24 1967

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-4278	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name	
2. Name of Operator Pennzoil Company ✓		8. Farm or Lease Name Yates-State	
3. Address of Operator 1007 Midland Savings Bldg., Midland, Texas 79701		9. Well No. 1	
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1650 FEET FROM THE West LINE, SECTION 32 TOWNSHIP 20-S RANGE 30-E NMPM.		10. Field and Pool, or Wildcat Wildcat - Wolfcamp	
15. Elevation (Show whether DF, RT, GR, etc.) 3663.6 GL		12. County Eddy	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

On July 26, 1967, the well was plugged and abandoned as follows:

Set cast iron bridge plug at 10,200' with 25 sack plug on top of bridge plug.

Cut off 4-1/2" casing at 6,600'.

Set 40 sack cement plug 6,680 to 6,480'.

Set 60 sack cement plug 4194 to 4000'. (Top of plug tagged with tubing)

Intermediate 8-5/8" casing was set at 4100'.

Hole was filled with 9# mud between all plugs.

Plugging was witnessed by Mr. John Havens with U. S. Geological Survey.

Well was released to U. S. Geological Survey to be used as an observation well.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Rodney C. Byrd TITLE Petroleum Engineer DATE July 27, 1967

APPROVED BY [Signature] TITLE Oil and Gas Supervisor DATE July 27, 1967

CONDITIONS OF APPROVAL, IF ANY: