

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN T
(Other instruc
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-07086

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT--" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER
2. NAME OF OPERATOR
PENNZOIL COMPANY
3. ADDRESS OF OPERATOR
1007 Midland Savings Building, Midland, Texas 79701
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
1980' FSL, 1650' FWL, Sec 33, T-20-S, R-30-E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Hudson-Federal 33

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Penn.

11. SEC., T., R., E., M., OR BLK. AND
SURVEY OR AREA

Sec 33, T-20-S, R-30-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3381.4 GL

12. COUNTY OR PARISH

Eddy

13. STATE

N. Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing and cementing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3-31-67: Spudded 20" hole at 7:30 p.m. Drilled to 505'. Ran 16 jts of 16" OD, 65#, H-40, ST&C casing to 504'. Cemented with 400 Sx Class C cement w/4% gel followed by 150 Sx Class C cement w/2% HA-5. Plug down at 4:45 p. m. 4-2-67. Cement circulated o.k. After 24 hours, started drilling.

4-5-67: Drilled 15" hole to 1445'. Base of salt at 1336'. Ran 35 jts of 11-3/4" OD, 42#, H-40 csg. to 1445'. Cemented with 900 Sx Incor w/32# salt per sack and 4% gel followed by 150 Sx Incor w/22# salt per sack and 2% HA-5. Plug down at 11:45 a. m. 4-5-67. Cement circulated o.k. After 24 hours, tested casing with 1000# for 30 minutes. Tested o.k. Drilled plug at 12:15 p. m. 4-6-67.

RECEIVED

RECEIVED
APR 14 1967
U.S. GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Drilling Superintendent DATE 4-12-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED
APR 14 1967
R. L. BLECKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side