

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN TR  
(Other instruct.  
reverse side)

CATE\*  
on re-

Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-031397-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Yates Petroleum Corporation - H. T. Hilliard

3. ADDRESS OF OPERATOR

309 Carper Building - Artesia, New Mexico 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

Unit Letter 'H-1650' FNL & 660' FEL  
Section 14-21S-22E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Tex. Pacific "BF"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

14-21S-22E NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4139' GL

12. COUNTY OR PARISH

Eddy

13. STATE

N. Mex.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded 17-1/4" hole at 5:15 P.M. 5-18-67.

Ran 5 jts. (162') of 13-3/8" casing set at 162' and cemented with 200 sacks of cement. Plug down at 8:30 A.M. 5-19-67. Cemented with 50 sacks of regular 4% cement, 1/4# flocele per sx and 2% CaCl, 150 sacks of Class "C" 4% gel, 1/4# flocele per sx and 2% CaCl. Cement circulated to the surface. WOC 14-1/4 hours. Nippled up and resumed drilling.

RECEIVED

MAY 24 1967

O. C. C.  
ARTESIA, OFFICE

RECEIVED  
MAY 22 1967  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*M. L. Armstrong*

TITLE

Agent

DATE

5-22-67

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED  
MAY 23 1967  
R. L. BEEKMAN  
DISTRICT ENGINEER

\*See Instructions on Reverse Side

