

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Harvey E. Yates Company
3. ADDRESS OF OPERATOR
P. O. Box 1933, Roswell, NM 88201
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990' FNL & 330' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

5. LEASE NM-03677	RECEIVED BY AUG 23 1984 O. C. D. ARTESIA, OFFICE
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Stebbins Deep Federal	
9. WELL NO. 4	
10. FIELD OR WILDCAT NAME Scanlan-Delaware	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 30, T-20S, R-29E	
12. COUNTY OR PARISH Eddy	13. STATE NM
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 3250' GL	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7/28/84 Clean out hole from 803' to 3364'.
8/01/84 Run 9.5# 4 1/2" csg to 3352' w/DV tool @ 2020'. Pump 385 sxs class "C" cmt. on first stage, on second stage pump 585 sxs class "C" cmt. Circ 10 sxs.
8/03/84 Perf from 3285'-86', 3299', 3300-01', 3306'-08'. (9 holes). Spot 200 gal acid. Acidize w/200 gal 7 1/2% MCA.
8/04/84 Acidize w/1000 gal 7 1/2% MCA
8/07/84 Frac w/20,000 gal 70% quality methynol on frac.
8/08/84 Hang well on pump.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Reservoir Engineer DATE 8/20/84

ACCEPTED FOR RECORD (This space for Federal or State office use)

APPROVED BY [Signature] AUG 22 1984

CONDITIONS OF APPROVAL

[Signature] NEW MEXICO

*See Instructions on Reverse Side