

Form 9-331  
(May 1963)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUBMIT IN PLICATE  
(Other instructions on reverse side)

Form approved  
Budget Bureau No. 45-11-11

5. LEASE DESIGNATION AND SERIES NO.

NM 05551

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		7. UNIT AGREEMENT NAME North Indian Basin Unit
2. NAME OF OPERATOR Marathon Oil Company		8. FARM OR LEASE NAME North Indian Basin Unit
3. ADDRESS OF OPERATOR P.O. Box 220, Hobbs, New Mexico 88240		9. WELL NO. 7
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1650' FSL and 1650' FWL		10. FIELD AND POOL, OR WELLCAT Undesignated (Indian Basin Upper Penn)
14. PERMIT NO.		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 11-21S-23E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) GL 3766.8'		12. COUNTY OR PARISH Eddy
		13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

Cement intermediate casing x  
(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to 2100'. Ran 66 jts. of 8-5/8" casing, effective length, 2079.87', overall length, 2100.33'. Set from 14.90' to 2098'. Last setting depth includes Baker float collar and guide shoe - 3.23'. Bottom 3 jts. Baker locked and bottom 200' covered with centralizers. Baskets set @ 776', 619', 515', and 481'. Displaced casing with fresh water and washed 5' to bottom. Cemented by Halliburton with 1300 sacks Trinity light weight cement with 12 1/2# Gilsonite per sack followed by 200 sacks Class A cement with 2% Cal. Chloride. Pump pressure 800#. Final 1500#. Circulated between 400 and 500 sacks cement to pit. W.O.C. 24 hrs. Pressured up on casing to 2000#, held O.K. for 30 minutes.

RECEIVED  
OCT 23 1967  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. A. Hill Jr.

TITLE

Area Supt.

DATE

10-19-67

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side

Dist.: CoPL: LHS: BGH: Phillips: Monsanto: Sinclair; File