

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0251

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. **RECEIVED**

OIL WELL ☐ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
PAN AMERICAN PETROLEUM CORPORATION

DEC 15 1967

3. ADDRESS OF OPERATOR
BOX 68, HOES, N. M. 88240

O. C. C.

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

7. UNIT AGREEMENT NAME

BIG EDDY UNIT Federal

8. FARM OR LEASE NAME

9. WELL NO.

11

10. FIELD AND POOL, OR WILDCAT

WILDCAT

11. SEC., T., R., M., OR BLK., AND SURVEY OR AREA

7-20-31 NMPM

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3505' R. D. B.

12. COUNTY OR PARISH

EDDY

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Drilled well to a total depth of 11890' and evaluated the Atoka. Now commercial. Propose to plug back, set casing and attempt Delaware sand completion. Plugback will be accomplished by setting cement plugs: 100# @ 11,600'; 50# @ 10,540'; 50# @ 9020'; 50# @ 7000'; 4 1/2" OD 9.5# J-55 casing will be run and set @ approx 5525' w/ 400# Incon. Interval 5142-65 will be perforated and evaluated.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

024- USGS- 48
1- NSID
1- SUSP
1- RRI
1- STATE LAND
1- PERRY BASS

APPROVED
DEC 14 1967
R. L. DEWILMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

RECEIVED
DEC 13 1967
GEOLOGICAL SURVEY
ALBUQUERQUE, NEW MEXICO