

NO. OF COPIES RECEIVED	4
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	2

RECEIVED
NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

30-015-20138

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
L-185	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator		Cawley Unit
3. Address of Operator		8. Farm or Lease Name
P. C. Box 1978, Roswell, New Mexico 86201		Cawley Unit
4. Location of Well		9. Well No.
UNIT LETTER F , 1800 FEET FROM THE North LINE AND 1980 FEET FROM		1
THE West LINE, SECTION 10 TOWNSHIP 22-S RANGE 22-E N.M.P.M.		10. Field and Pool, or Wildcat
		Wildcat
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4357' DF		Eddy

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

Drilled 7-7/8" hole to 7610' TD. Two DST's in Wolfcamp and three DST's in Cisco and logs proved the well to be non-commercial. We propose to plug and abandon by setting the following cement plugs:

30 sx	7510-7610	(Cisco Canyon)
30 sx	7200-7300	(Cisco Canyon)
30 sx	6400-6500	(Wolfcamp)
60 sx	4860-5060	(Wolfcamp)
30 sx	3250-3350	(Bone Springs)
30 sx	1750-1850	(Across 8-5/8" casing shoe)
10 sx	10- 50	In top of well.

9.0# mud will be left between all cement plugs. Both 13-3/8" and 8-5/8" casing strings will be left intact.

Above program verbally approved by Mr. R. L. Stamets.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Original Signed
A. D. Kloxin TITLE Dist. Prod. & Drlg. Supt. DATE 6-10-68

APPROVED BY W. A. Gressett TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: