

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

30-015-20200

5a. Indicate Type of Lease	State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	E-997
7. Unit Agreement Name	
8. Farm or Lease Name	Eddy "BD" State
9. Well No.	1
10. Field and Pool, or Wildcat	Undesignated
12. County	Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	2. Name of Operator
Gulf Oil Corporation	3. Address of Operator
Box 670, Hobbs, New Mexico 88240	4. Location of Well
UNIT LETTER <u>P</u> , <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>990</u> FEET FROM THE <u>East</u> LINE, SECTION <u>32</u> TOWNSHIP <u>20-S</u> RANGE <u>30-E</u> NMPM.	15. Elevation (Show whether DF, RT, GR, etc.)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Cactus Drilling Corporation spudded 20" hole at 11:30 AM, January 21, 1969. Drilled to 440'. Ran 11 joints, 438' of 16" 65# H-40 ST&C casing set and cemented at 435' with 450 sacks of Class C with 4% gel, 2% Ca Cl2 and 150 sacks of Class C with 2% Ca Cl2. Cement circulated. WOC 15 hours. Tested casing with 600#, 30 minutes. OK. WOC total of 24 hours. Started drilling 15" hole at 440' at 3:00 PM, January 25, 1969.

RECEIVED

JAN 28 1969

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

ORIGINAL SIGNED BY
C. D. BORLAND

SIGNED

TITLE Area Production Manager

O. C. C.
ARTESIA, OFFICE

DATE January 27, 1969

APPROVED BY W. A. Gussett
CONDITIONS OF APPROVAL, IF ANY:

TITLE OIL AND GAS INSPECTOR

DATE JAN 30 1969