

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Haganan P.T. Corp.</u>		Lease <u>State Com</u>		Well # <u>1</u>	
Location of Well	Unit <u>G</u>	Section <u>15</u>	Township <u>21</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor <u>Moran</u>	1980 N & E		Type of Equipment <u>Rotary</u>		

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>20</u>	<u>16</u>	<u>47.22</u>		<u>100</u>	<u>150</u>
<u>13 3/4 1000</u> <u>12 1/4 2700</u>	<u>9 5/8</u>	<u>32.3 & 36</u>	<u>New</u>	<u>2700</u>	<u>1050</u>
<u>8 3/4</u>	<u>5 1/2 or 7"</u>	<u>17 or 23 & 26</u>		<u>ID</u>	<u>750 ±</u>

Casing Data:

Surface 59 joints of 9 5/8 inch 36 # Grade H

(Approved) (Rejected) 5-2-69

Inspected by R.D. Stewart date 5-2-69

Cementing Program

Size of hole 13 3/4 1108 Size of Casing 9 5/8 Sacks cement required

Type of Shoe used Texas Float collar used insert Btm 3 jts welded Thred lock

TD of hole 2706 Set Feet of 9 5/8 Inch 36 # Grade H

New-used csg. @ ID with ? sacks neat cement around shoe

+ ? sax additives

Plug down @ (AM) (PM) Date

Cement circulated No. of Sacks

Cemented by Witnessed by

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks:

See attached sheet

Flow of black sulphur water at 786'. Very little water reported above this point. 24 hour fill at 164' was 6 inches.