

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.

NM 3047

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal "28"

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

11. SECTION, R., M., OR BLK. AND SURVEY OR AREA

Sec. 28, T-21-S, R-21-E

12. COUNTY OR PARISH

Eddy

N. M.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Pennzoil United, Inc.

3. ADDRESS OF OPERATOR

P. O. Drawer 1828 - Midland, Texas

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

1980 FNL & 1980 FEL of Section 28, T-21-S, R-21-E
Eddy County, New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4790' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

Commence operations

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-9-69 Drilled 18 1/2" hole to 48'. - Ran 16" OD, 65# casing to 48'. - Cemented w/5 yds. ready mix to the surface.

8-14-69 Moved in rotary rig. - Spudded 12 1/4" hole @ 7:00 p.m.

8-20-69 Drilled to 1680'. - Ran 9 5/8" OD, 40# casing to 1680'. - Cemented w/450 sx Class "C" 4% gel with 12 1/2# gilsonite & 1/2# flocele per sack plus 150 sx Class "C" w/1/2# flocele & 2% CaCl per sack. Cement did not circulate. After 6 hrs, ran temperature survey. Top cement 425'. - Cemented outside thru 1" pipe w/a total of 325 sx Class "C" w/2% CaCl. Cement circulated to the surface. - Job complete @ 12:00 noon 8-21-69.

8-22-69 After 18 hrs WOC, tested casing w/1500# for 30 minutes. - Tested O.K.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Superintendent

DATE

9-12-69

(This space for Federal or State use)

APPROVED BY

CONDITIONS OF APPROVAL ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES
SEP 16 1969
Date
ACTING District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.