

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Gulf Oil Corporation	8. FARM OR LEASE NAME Helbing Federal
3. ADDRESS OF OPERATOR Box 670, Hobbs, New Mexico 88240	9. WELL NO. 3
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	10. FIELD AND POOL, OR WILDCAT Undesignated
	11. SEC. T. R. MC. OR BEK. AND SURVEY OF AREA Sec 15, 22-S, 23-E
14. PERMIT NO.	12. COUNTY OR PARISH 13. STATE Eddy New Mexico
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4137' OL	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Abbott Brothers drilled 12-1/4" hole to 30' with rat hole machine and cemented to 18'. Ran 1 joint of 13-3/8" OD 48# H-40 ST&C casing, set and cemented at 30'. Cement circulated.

Moran Drilling Company spudded 12-1/4" hole at 30' at 1:00 PM, March 1, 1970. Drilled to 900'. Ran 28 joints, 870' of 8-5/8" OD 24# K-55 ST&C casing set and cemented at 800' with 350 sacks of Class C with 12.5% gilsonite per sack, 4% gel, 2% Ca Cl2 and 100 sacks of Class C with 2% Ca Cl2. Witnessed by Mr. Leon Beckman with USGS in Artesia. TS indicated TOC at 730'. Cemented thru 3/4" pipe down annulus with 50 sacks of Class C with 2% Ca Cl2 and 1/2# Floccal per sack. TOC at 730'. Cemented with 50 sacks of Class C with 2% Ca Cl2 and 1# cottonseed hulls. TOC at 730'. Cemented with 8 yards of ready mix concrete with 3/8" gravel and 2% Ca Cl2. TOC at 416'. Cemented with 230 sacks of Class C with 2% Ca Cl2. TOC at 344'. Cemented with 7.5 yards of ready mix concrete with 3/8" gravel with 2% Ca Cl2. Cemented to surface. WOC 4 1/2 hours. Tested casing with 1000#, 30 minutes, OK.

Started drilling 7-7/8" hole at 900' at 1:AM, March 6, 1970.

RECEIVED

MAR 9 1970

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

C. D. BORLAND

TITLE

D. C. C.

Area Production Manager

DATE

March 6, 1970

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

ACCEPTED FOR RECORD PURPOSES
MAR - 9 1970

Date

ACTING District Engineer

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued from the local, Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones or other zones with present significant fluid contents, not separated by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; and of other material placed below, between and above plugs; reasons for, method of, and date of, any casing, liner or tubing pulled; and the date to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1965 O-685229

See instructions on reverse side

APPROPRIATE AGENCIES AND FIELD OFFICES
MAY 1965
ACTION REQUIRED

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY
SUMMARY NOTICES AND REPORTS ON WELLS

Form G-201
(2-6-64)

RECEIVED
MAR 19 1965
U.S. GEOLOGICAL SURVEY

RECEIVED
MAR 19 1965
U.S. GEOLOGICAL SURVEY

RECEIVED
MAR 19 1965
U.S. GEOLOGICAL SURVEY

RECEIVED
MAR 19 1965
U.S. GEOLOGICAL SURVEY