

NO. OF COPIES RECEIVED	6
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	2
LAND OFFICE	1
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION RECEIVED

Form C-101
Revised 1-1-65

AMENDED

NOV 13 1970

D. C. S.

ARTESIA, OFFICE

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work DRILL <input checked="" type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/>		5A. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
b. Type of Well OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>		5. State Oil & Gas Lease No. K-675 & Fee	
2. Name of Operator Corinne Grace		7. Unit Agreement Name	
3. Address of Operator c/o Oil Reports & Gas Services, Inc., Box 763, Hobbs, N. M. 88240		8. Farm or Lease Name City of Carlisbad	
4. Location of Well UNIT LETTER 0 LOCATED 660 FEET FROM THE South LINE AND 1980 FEET FROM THE East LINE OF SEC. 25 TWP. 22S RGE. 26E NMPM		9. Well No. 1	
		10. Field and Pool, or Wildcat Wildcat	
		12. County May	
		19. Proposed Depth 12,100	
		19A. Formation Morrow	
		20. Rotary or C.T. Combination	
21. Elevations (Show whether DF, RT, etc.) 3206.1 GL		21A. Kind & Status Plug. Bond Blanket	
		21B. Drilling Contractor Delta Drilling Co.	
		22. Approx. Date Work will start 9/15/70	

23.

PROPOSED CASING AND CEMENT PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF CEMENT	EST. TOP
17 1/2	13 3/8	54#	364	500	Circ
12 1/4	9 5/8	36#	5100	1400	Circ
7 7/8	5 1/2	15.5# & 17#	12,100	1400	6700

IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: IF PROPOSAL IS TO DEEPEN OR PLUG BACK, GIVE DATA ON PRESENT PRODUCTIVE ZONE AND PROPOSED NEW PRODUCTIVE ZONE. GIVE BLOWOUT PREVENTER PROGRAM, IF ANY.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Monica Keller Title Agent Date 11/13/70

(This space for State Use)

APPROVED BY W. A. Gressett TITLE OIL AND GAS DEVELOPER DATE NOV 13 1970

CONDITIONS OF APPROVAL, IF ANY:

Cement must be circulated to surface behind 13 3/8" & 9 5/8" casing