

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Commission not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka <u>9735</u>	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____	T. Miss Lm. <u>10890</u>	T. Cliff House _____	T. Leadville _____
T. 7 Rivers _____	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen _____	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____	T. Simpson _____	T. Gallup _____	T. Ignacio Qtzte _____
T. Glorieta _____	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinbry _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Tubb _____	T. Granite _____	T. Todilto _____	T. _____
T. Drinkard _____	T. Delaware Sand <u>1682</u>	T. Entrada _____	T. _____
T. Abo <u>3rd BS 7526</u>	T. Bone Springs <u>4150</u>	T. Wingate _____	T. _____
T. Wolfcamp <u>7850</u>	T. Morrow <u>10187</u>	T. Chinle _____	T. _____
T. Penn. <u>8785</u>	T. Barnett <u>10570</u>	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn. "A" _____	T. _____

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1680	1680	Dol., Lm., Sd.	DST #1	8785-8825	Op. 1 hr., GTS 12",	
1680	4150	2470	Sd., sh., & dolo.			TSTM, Rec. 3318' sul. wtr.	
4150	7525	3375	Lm., sd., sh.			HP 3961-3961, 30" ISI 3410#,	
7525	7850	325	Sd., sh.			45" FSI 3410#, FP 586-1476#.	
7850	8785	935	Sh., Lm.	DST #2	10202-370"	Op. 2½ hrs., GTS	
8785	9100	315	Lm., sh., & dolo.			8", SFP 22#/3/4" ck./920 MCF.	
9100	10570	1470	Lm., sh. & sd.			Rec. 500' SGCM. HP 4727-4727#,	
10570	10890	320	Sh.			FP 184-218#, 45" ISI 3546# (?),	
10890	10905	15	Lm., Sh.			2' FSI 4295#.	
				DST #3	10470-520	Op. 2 hrs., GTS 6	
						SFP 42#/1" ck. @ 1,450 MCF.	
						Rec. 100' HGCM, HP 4897-4867#,	
						FP 268-299#, 45" ISI 4412#,	
						90" FSI 4443#, Temp. 187°.	