

ARTESIA OIL CONGRESSION DISTRICT
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Cities Service Oil Co.</i>		Lease <i>State Oil Co.</i>		Well # <i>1</i>	
Location of Well	Unit <i>1650 S.E.</i>	Section <i>36</i>	Township <i>22</i>	Range <i>24</i>	County <i>El Paso</i>
Drilling Contractor	<i>Sonny Southland</i>		Type of Equipment <i>Rotary & Start oppt. 4-1-71</i>		
<u>APPROVED CASING PROGRAM 3-26-71</u>					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>1 1/4"</i>	<i>8 7/8"</i>	<i>24</i>		<i>2500</i>	<i>air</i>
<i>8 7/4"</i>	<i>5 1/2"</i>	<i>17</i>		<i>10000</i>	<i>400</i>
Casing Data:					
Surface _____ joints of _____ inch # Grade _____					
(Approved) (Rejected)					
Inspected by _____ date _____					
Cementing Program					
Size of hole <i>12 1/4" - 700</i> Size of Casing <i>8 7/8"</i> Sacks cement required _____					
Type of Shoe used <i>Shoe</i> Float collar used <i>yes</i> Btm 3 jts welded <i>Three Lbs</i>					
ID of hole <i>2500</i> Set <i>2499</i> Feet of <i>8 7/8" inch 24</i> # Grade <i>K-5 24"</i>					
New-used csg. @ <i>2499</i> with <i>150</i> sacks neat cement around shoe					
+ <i>780</i> sack <i>Halliburton</i> additives + <i>5 lb Silica 14 1/2 sacks 27000</i>					
Plug down @ <i>1,000</i> (AM) (PM) Date <i>4-8-71</i>					
Cement circulated <i>no</i> No. of Sacks _____					
Cemented by <i>Stewart - Halliburton</i> Witnessed by _____					
Temp. Survey ran @ <i>10:45</i> (AM) (PM) Date <i>4-8-71</i> top cement @ <i>300</i>					
Casing test @ _____ (AM) (PM) Date _____					
Method Used _____ Witnessed by _____					
Checked for shut off @ _____ (AM) (PM) Date _____					
Method used _____ Witnessed by _____					
Remarks: <i>I w/ air. first w/ c 751 used 6 centralizers</i>					
<i>1" to 303 - Picked up to 288 - Cement 3000 Incon Prg - 27000 47000 11:55 AM.</i>					
<i>1" to 197 - Cement w/ ⁹⁰ sack Incon Prg - 27000 2100 PM.</i>					
<i>Pulling 400' but 1 ft. 1" filled to surface. Had fell back approx. 40'</i>					