

NO. OF COPIES RECEIVED	11
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MAY 12 1971

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6460	
7. Unit Agreement Name	
8. Farm or Lease Name State CN Com.	
9. Well No. 1	
10. Field and Pool, or Wildcat Rock Tank L. Morrow	
12. County Eddy	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☐ OTHER- **Dry Hole**

2. Name of Operator
Cities Service Oil Company

3. Address of Operator
Box 69 - Hobbs, New Mexico 88240

4. Location of Well
UNIT LETTER **J**, **1650** FEET FROM THE **South** LINE AND **1650** FEET FROM THE **East** LINE, SECTION **36** TOWNSHIP **22S** RANGE **24E** NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)
3914 DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☒

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 10858 Shale. Prep. to P & A. We propose to plug and abandon the above well in the following manner:

1. Load hole with mud laden fluid.
2. Displace a 35 sack cement plug @ approx. 10550-10450 (across the top of the Morrow)
3. Displace a 50 sack cement plug @ approx. 9812-9650 (across DST #2 interval 9670-9803)
4. Displace a 35 sack cement plug @ approx. 8600-8500 (across DST #1 interval 8525-8574)
5. Displace a 35 sack cement plug @ approx. 7600-7500 (across the top of the Dean @ 7540)
6. Displace a 35 sack cement plug @ approx. 6500-6400.
7. Displace a 35 sack cement plug @ approx. 5000-4900.
8. Displace a 35 sack cement plug @ approx. 2850-2750 (across water zone @ 2736)
9. Displace a 35 sack cement plug @ approx. 2550-2450 ($\frac{1}{2}$ in and $\frac{1}{2}$ out of 8 5/8" csg. set and cemented @ 2499 w/930 sacks)
10. Displace a 10 sack cement surface plug @ approx. 30'-0 w/a dry hole marker to designate a plugged and abandoned location.

The above plugging procedure was verbally approved by Mr. Bill Gressett on May 7, 1971.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED _____	TITLE District Admin. Supervisor	DATE May 11, 1971
APPROVED BY <u>W. A. Gressett</u>	TITLE OIL AND GAS INSPECTOR	DATE MAY 13 1971
CONDITIONS OF APPROVAL, IF ANY:		