

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPI
(Other instructions
verse side)TE*
re-Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME Springa Unit
2. NAME OF OPERATOR Gulf Oil Corporation	8. FARM OR LEASE NAME
3. ADDRESS OF OPERATOR Box 670, Hobbs, New Mexico 88240	9. WELL NO. 5
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1650' FWL, Section 35, 20-S, 26-E	10. FIELD AND POOL, OR WILDCAT Springa & Upper Perm Gas
14. PERMIT NO.	11. SEC., T., R., OR BLM. AND SURVEY OR AREA Sec 35, 20-S, 26-E
15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3252' GL	12. COUNTY OR PARISH Eddy
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT

(NOTE: Report results of multiple completion or Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 30' of 20" spiral weld conductor casing with Rat Hole machining on August 16, 1971. Delta Drilling Company spudded 17-1/2" hole at 10:30 AM, August 19, 1971. Drilled to 265'. Ran 3 joints and one cut joint, 253' of 13-3/8" OD 48# H-40 ST&C casing set and cemented at 265' with 250 sacks of Class C cement containing 2% Ca Cl₂. Cement circulated. WOP & NU 22 hours. Tested casing with 600#, 30 minutes, OK.

Started drilling 11" hole at 265' at 10:30 PM, August 20, 1971.

RECEIVED

AUG 25 1971

O. C. C.
ARTESIA, OFFICE

18. I hereby certify that the foregoing is true and correct

SIGNED ORIGINAL SIGNED BY
C. D. BORLANDTITLE **Area Production Manager**DATE **August 23, 1971**

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL IF ANY:

TITLE

DATE

APPROVED

AUG 24 1971

R. L. BEEKMAN

ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1965 O-685229
GPO 937-499

967-851