

N. M. O. C. C. COPY
UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPlicate
(Other instructions on reverse side)

Copy to SR
Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐		5. LEASE DESIGNATION AND SERIAL NO. NM-0339758
2. NAME OF OPERATOR Gulf Oil Corporation		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 670, Hobbs, New Mexico 88240		7. UNIT AGREEMENT NAME Springs Unit
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1650' FWL, Section 35, 20-S, 26-E		8. FARM OR LEASE NAME
14. PERMIT NO.		9. WELL NO. 5
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3252' GL		10. FIELD AND POOL, OR WELDCAN Springs - Upper Joint Gas
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC. T. R. M. OR MEX. AND SURVEY OF AREA Sec 35, 20-S, 26-E
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and names pertinent to this work.)*		12. COUNTY OR PARISH 13. STATE Eddy New Mexico

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
 FRACTURE TREAT ☐
 SHOOT OR ACIDIZE ☐
 REPAIR WELL ☐
 (Other) ☐

PULL OR ALTER CASING ☐
 MULTIPLE COMPLETE ☐
 ABANDON* ☐
 CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒
 FRACTURE TREATMENT ☐
 SHOOTING OR ACIDIZING ☐
 (Other) ☐

REPAIRING WELL ☐
 ALTERING CASING ☐
 ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Delta Drilling Company completed 11" hole at 2750' at 12:30 PM, August 27, 1971. Ran 85 joints and one cut joint 2737' of 8-5/8" OD 21# K-55 ST&C casing set and cemented at 2750' with 760 sacks of Class C with 1% gel and 2% Ca Cl and 100 sacks of Class C with 2% Ca Cl2. Cement circulated. Witnessed by Charles Sanderson with U. S. G. S. WOC and NU over 21 hours. Tested casing with 1500#, 30 minutes, OK.

Started drilling 7-7/8" hole at 2750' at 1:30 AM, August 29, 1971.

RECEIVED

SEP 2 1971

D C C
ARTESIAL DIVISION

18. I hereby certify that the foregoing is true and correct

SIGNED C. F. KALTEYER

TITLE Area Petroleum Engineer

DATE August 30, 1971

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE _____

APPROVED

SEP - 1 1971
H. L. BECKMAN
SEAL

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1980-40-685229
GPO 897-499 897-851

DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
WELL ABANDONMENT REPORTS

WELL ABANDONMENT REPORTS

WELL ABANDONMENT REPORTS