

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT INSTRUCTIONS ON REVERSE SIDE

Budget Bureau No.

5. LEASE DESIGNATION AND SERIAL NO.

NY-0338758

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Dry hole JAN 27 1972

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

Box 670, Hobbs, New Mexico 88240

ARTESIA, OFFICE

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)
At surface

660' FNL & 1650' FWL, Section 35, 20-S, 26-E

7. UNIT AGREEMENT NAME

Springs Unit

8. FARM OR LEASE NAME

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Undesignated

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 35, 20-S, 26-E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3252' GL

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other) Plug and Abandon

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8125' TD, 2711' FB.

Pull tubing, rods and pump. Load hole with heavy mud. Spot 38 sack Class H cement plug from 2600' to 2470', across 8-5/8" perforations 2522' to 2560'. Spot 30 sack Class H cement plug from 1960' to 1850', across 8-5/8" perforations 1898' to 1909'. Spot 16 sack Class H cement plug from 50' to surface. Install dry hole marker and clean location.

RECEIVED

JAN 26 1972

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Engineer

DATE January 25, 1972

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

APPROVED
JAN 26 1972
R. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side