	1-12 IVIA 1040 U.	· C. CLITY	$\ell^{*}\star j$
(Mag 1963)	L ILU STATES	SUBMIT IN TR. ATE	Budget Bureau No. 42-1114
DEPA	ARTMENT OF THE INTERI	UK verse side)	5. LEASE DESIGNATION AND SERIAL NO
	GEOLOGICAL SURVEY		NM-0338758 6. IF INDIAN, ALLOTTEE OR TRIBE NAM
	NOTICES AND REPORTS C		G. IF INDIAN, ALLOTTEE OR TRIBE NAM
(Do not use this form for Use "AF	proposals to drill or to deepen or plug be PPLICATION FOR PERMIT—" for such pre-	ack to'a different reservoir. oposals.)	
1.	F	RECEIVED	7. UNIT AGREEMENT NAME
	HER Dry Hole	·	Springs Unit
2. NAME OF OPERATOR		0.017 + 6 1972	8. FARM OR LEASE NAME
Gulf Oil Corporatio 3. ADDRESS OF OPEBATOR	<u>m </u>		9. WELL NO.
Box 670, Hobbs, New	v Mexico 88240	n (2, 2).	5
	y Mexico 88240 ation clearly and in accordance with any S	State requirements FICE	10. FIELD AND POOL, OR WILDCAT
At surface		_	Wildcat 11. SEC., T., R., M., OB BLK. AND
660' FNL & 1650' FW	NL, Section 35, 20-S, 26-	E	SURVEY OR AREA
			Sec 35. 20-S 26-E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF,	RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	3252' GL	······································	Eddy New Mex
18. Chec	k Appropriate Box To Indicate No	ature of Notice, Report, or C	Other Data
NOTICE OF	INTENTION TO :	SUBSEQ	UENT REPORT OF :
TEST WATER SHUT-OFF	PULL OR ALTER CASING	WATER SHUT-OFF	REPAIRING WELL
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING CASING
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT [®] XX
REPAIR WELL	CHANGE PLANS	(Other)	s of multiple completion on Well
(Other)		Completion or Recomp	letion Report and Log form.)
25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s	ED OPERATIONS (Clearly state all pertinent directionally drilled, give subsurface locati and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5≠8" casing perforati
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562', Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is o nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro ping and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotte	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. It well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotte d cleaned location. P	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562', Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotte d cleaned location. P	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972.	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro oing and spotted 30 s 98' to 1909'. Spotted d cleaned location. P	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972. RECEN U. S. GENLOWSAL ARTESIA, NEW M	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark
<pre>proposed work. If well is onent to this work.)* 25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotted d cleaned location. P 18. I hereby certify that the foregometry I8. I hereby certify that the foregometry (This space for Federal or State)</pre>	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972. RECEN U. S. GENLOWSAL ARTESIA, NEW M	with 8.6# mud. Spotte 2522' to 2562', Raised -5#8" casing perforati Installed dry hole mark
<pre>proposed work. If well is on nent to this work.)* 25' TD. Pulled rods, pump sack cement plug frobing and spotted 30 s 98' to 1909'. Spotted d cleaned location. P 18. I hereby certify that the foregoes IGNED</pre>	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972. RECEN U. S. GENLOWSAL ARTESIA, NEW M	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotted d cleaned location. F 18. I hereby certify that the foregone SIGNED	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	g and circulated hold 8-5/8" perforations 0' to 1861; across 8 om 50' to surface. ruary 15, 1972. RECEN U. S. GENLOWSAL ARTESIA, NEW M	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotted d cleaned location. F 18. I hereby certify that the foregone SIGNED	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb 'lugged and abandoned Feb 'lugged and correct TITLE Are te office use)	a Engineer	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
 proposed work. If well is a nent to this work.)* 25' TD. Pulled rods, pump sack cement plug frobing and spotted 30 s 98' to 1909'. Spotted d cleaned location. F d cleaned location. F 18. I hereby certify that the foreg SIGNED (This space for Federal or Sta APPROVED BY CONDITIONS) STATEBOAL, 	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb	a Engineer	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2
25' TD. Pulled rods, pump sack cement plug fro bing and spotted 30 s 98' to 1909'. Spotted d cleaned location. F 18. I hereby certify that the foregone SIGNED	and tubing. Reran tubin om 2600' to 2475', across sack cement plug from 196 ed 16 sack cement plug fr 'lugged and abandoned Feb 'lugged and abandoned Feb 'lugged and correct TITLE Are te office use)	a Engineer	with 8.6# mud. Spotte 2522' to 2562'. Raised -5#8" casing perforati Installed dry hole mark 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2