

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

**RECEIVED**  
**NEW MEXICO OIL CONSERVATION COMMISSION**  
**SEP 15 1971**

Form C-103  
 Supersedes Old  
 C-102 and C-103  
 Effective 1-1-65

**O. C. C.**  
**ARTESIA, OFFICE**

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>

5. State Oil & Gas Lease No.  
 --

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
 USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name Catclaw Draw Unit
2. Name of Operator Hanagan Petroleum Corporation ✓		8. Farm or Lease Name Catclaw Draw Unit
3. Address of Operator P. O. Box 1737, Roswell, New Mexico 88201		9. Well No. 2
4. Location of Well UNIT LETTER <u>G</u> <u>1650</u> FEET FROM THE <u>North</u> LINE AND <u>1650</u> FEET FROM THE <u>East</u> LINE, SECTION <u>23</u> TOWNSHIP <u>21S</u> RANGE <u>25E</u> NMPM.		10. Field and Pool, or Wildcat Catclaw Draw Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3417' KB		12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data  
 NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
 TEMPORARILY ABANDON ☐  
 PULL OR ALTER CASING ☐  
 OTHER ☐

PLUG AND ABANDON ☐  
 CHANGE PLANS ☐  
 OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIATION WORK ☐  
 COMMENCE DRILLING OPNS. ☐  
 CASING TEST AND CEMENT JOBS ☒  
 OTHER ☐  
 ALTERING CASING ☐  
 PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9/13/71: TD 2080' - ran 53 jts. new 8-5/8" csg. 24# JE & 32# JS 8 Rd. ST&C API set @ 2080' w/guide shoe, insert float valve, 1 centralizer 1 jt. off bottom, DV pkr. cementing collar @ 994' and 1 basket @ 895'. 1st stage, 150 sx Howco light 2% CaCl 1/4# flocel + 150 sx. Class C 2% CaCl, cement circ. w/60 sx excess, plug down 6:05 A.M.; 2nd stage, 300 sx Howco light 2% CaCl 10# gilsonite 8# salt 1/4# flocel, cement circ. w/45 sx excess, plug down 6:45 A.M.

9/14/71: TD 2080' - drilled DV tool, press. up 1000# 30 mins., no press. drop, drilled plug 2:05 A.M. WOC 20 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Hugh E. Hanagan TITLE Vice President DATE 9/14/71

APPROVED BY W. A. Gressett TITLE OIL AND GAS INSPECTOR DATE SEP 15 1971

CONDITIONS OF APPROVAL, IF ANY: