



HALLIBURTON COMPANY  
DUNCAN, OKLAHOMA

RECEIVED

JUN 5 1972

D. C. C.  
ARTEGIA, OFFICE

MEASURING LINE

# TEMPERATURE SURVEY

COMPANY Hewitt & Packard Co  
WELL NO. # 3 CAT CLAW DRILL  
POOL \_\_\_\_\_  
STATE N. MEX COUNTY Eddy  
SECTION \_\_\_\_\_

COMPANY \_\_\_\_\_  
WELL \_\_\_\_\_  
POOL \_\_\_\_\_  
COUNTY \_\_\_\_\_  
STATE \_\_\_\_\_  
FILE \_\_\_\_\_

LOG MEASURED FROM R.T.  
DRILLING MEASURED FROM R.T.  
PERMANENT DATUM \_\_\_\_\_

DATE OF CEMENTING 5-15-72 TIME 1550  
DATE OF SURVEY 5-16-72 TIME 0800  
AMOUNT OF CEMENT 600 TYPE H. L.  
150 C  
AMOUNT OF ADMIX 28% 10# TYPE C. C. GILSONITE  
14# 8# FLUOR, SALT

CASING SIZE 8 7/8 FROM 0 TO 2130 DIAM. OF HOLE 12 FROM 0 TO 2130  
FROM \_\_\_\_\_ TO \_\_\_\_\_ FROM \_\_\_\_\_ TO \_\_\_\_\_

SURVEY BEGINS AT R.T. FEET. ENDS AT 900 FEET.  
APPROX. CALCULATED FILL-UP OF \_\_\_\_\_ FT. BASED ON PERFECT HOLE AND ON AN AVERAGE OF \_\_\_\_\_ CU. FT. PER SACK OF SET CEMENT  
APPROX. TOP CEMENT 800 FEET. MAX. TEMP. 800 FEET.  
RECORDED BY C. Tubbs WITNESSED F. NEWTON

REMARKS OR OTHER DATA

TEMPERATURE IN DEGREES FAHRENHEIT

