

RECEIVED

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-63

SEP 26 1972
NEW MEXICO OIL CONSERVATION COMMISSION

O. C. C.
ARTESIA, OFFICE

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	1
FILE	1 ✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
K-4792-1

SHADRY NOTICES AND REPORTS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG IN A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT - 1 (FORM C-101) FOR NEW DRILLING.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐	7. Unit Agreement Name
2. Name of Operator	Catchlaw Draw Unit
Managan Petroleum Corporation	8. Name of Lease
3. Address of Operator	Catchlaw Draw Unit
P. O. Box 1737 - Roswell, New Mexico 88201	9. Well No.
4. Location of Well	6
UNIT LETTER J, 1650 FEET FROM THE South LINE AND 1650 FEET FROM	10. Field and Pool, or Wildcat
THE East LINE, SECTION 13 TOWNSHIP 21-S RANGE 25-E NMPM.	Catchlaw Draw Morrow
15. Elevation (Show whether DF, RT, CR, etc.)	12. County
3304 GR	Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-06-72 Spud 9:30 AM, Moran Drilling Contractor.
9-07-72 TD 307' (17 1/2" hole). Ran 9 jts. 13-3/8" 61# csg. set @ 307', cmt. w/350 sx Class C 1/2# floccel 2% CaCl, plug down 8:45 PM, cmt. didn't circ., filled 8 yds ready mix (1.32 slurry vol. cu. ft./sx, 800 temp slurry mixed, est. fm. temp. @ 750, compressive strength 575# 12 hrs.
9-08-72 Drilled plug 9:15 AM (WOC 12 1/2 hrs) press. up 600# 30 mins., no press. drop.
9-11-72 TD 1970' (11" & 12 1/2" hole), ran 49 jts. 24# ST&C set @ 1970', cmt. w/600 sx ROMCO light 1/2# floccel 5# gilsonite 2% CaCl + 150 sx Class C 1/2# floccel 2% CaCl, plug down @ 4:15 PM, cmt. didn't circ., ran temp. survey, top cmt. @ 350'. Circ. cmt. w/1" tbg. w/125 sx Class C 1/2# floccel 2% CaCl.
9-12-72 Drld. plug 11:45 AM (WOC 13 hrs.) press. up 1000# 30 mins., no press. drop.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>W. A. Gressett</u>	TITLE <u>Vice President</u>	DATE <u>9-25-72</u>
APPROVED BY <u>W. A. Gressett</u>	TITLE <u>OIL AND GAS INSPECTOR</u>	DATE <u>SEP 27 1972</u>
CONDITIONS OF APPROVAL, IF ANY:		