

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 10
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator David Fisher		Lease Arden State		Well # 1	
Location of Well	Unit 1400's 1620W	Section 7	Township 21	Range 26	County
Drilling Contractor Warton Drilling Co.		Type of Equipment Rotary to start 9-12-72			
APPROVED CASING PROGRAM					
Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
17 1/2"	13 3/8"	48-H-40		350	300 cu.
12 1/4"	9 5/8"	40-J-55		2300	1000 cu.
8 3/4"	4 1/2"			10900	450
Casing Data:					
Surface 70 joints of 9 5/8 inch 36 C # Grade J-55					
(Approved) (Rejected)					
Inspected by L. A. G. Morris date 9-22-72					
Cementing Program					
Size of hole 17 1/2" to 470 Size of Casing 9 5/8 Sacks cement required 450/sk					
Type of Shoe used Guide Float collar used insert Btm 3 jts welded Thread lock					
TD of hole 2327 KB Set 2309 Feet of 9 5/8 Inch 36 C # Grade J-55					
Used used csq. @ 2309 with 450 sacks neat cement around shoe Class C					
+ 1/2" Floccil sax 2% CC adding 14.8 #					
Plug down @ 145 (AM) (PM) Date 9-23-72					
Cement circulated N/C No. of Sacks N/A					
Cemented by Hall Liberton Witnessed by L. A. Morris					
Temp. Survey ran @ 6:45 (AM) (PM) Date 9-23-72 top cement @ 1350					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: Note kept a fluid level approximately 260'					
11:00 AM. 9-23-72 to 7:30 PM. 9-24-72					
*Cemented in 6 stages using a total of 1900 sx Class C + Floccil + CC					
" " 3 stages using 24 yards of 6 sx already mix.					