

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TWO COPIES
(Other instructions on reverse side)

Form approved
Budget Bureau No. 43-21434

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER Dry hole		5. LEASE DESIGNATION AND SERIAL NO. NM 03215	
2. NAME OF OPERATOR Tesoro Petroleum Corporation		6. INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 8520 Crownhill, San Antonio, TX 78209		7. UNIT ASSIGNMENT NAME Federal 28 Gas Com.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1200' FEL and 660' FSL of Section 28, T-20-S, R-26-E, NMP		8. FARM OR LEASE NAME Federal 28 Gas Com.	
14. PERMIT NO. Not available		9. WELL NO. 1	
15. ELEVATIONS (Show whether DP, RT, GR, etc.) 3232' GR 3244 KB		10. FISH AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA NMP Sec. 28, T-20-S, R-26-E	
		12. COUNTY OR PARISH Eddy	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11-15-72 Spudded. Set 13-3/8" casing at 220' KB. Circulated.
11-22-72 Drilled to 2642'. Set 8-5/8" at 2642' KB with 650 sx of DLW and 200 sx Class "C". Temperature log showed cement top between 700' and 800'.
Ran 1" to 600' and cemented with 200 sx Class "H". Tagged cement top with 1" at 250'. Cemented with 100 sx Class "H" and got returns.
12-6-72 Drilled to 8425'. DST at 8370' - 8425'. Weak blow and dead in 12 minutes.
Recovered 550' muddy water and 1285' clear water with strong H₂S odor.

Propose to abandon. Will set plugs:

8300' - 8400'
7600' - 7700'
5700' - 5800'
4000' - 4100'
2600' - 2700'
20' in surface

RECEIVED
DEC 11 1972
U. S. GEOLOGICAL SURVEY
ARTESIA NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Mgr. Production Engineering DATE 12-8-72

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE