

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.
5. LEASE DESIGNATION AND SERIAL NO.**NM 16082**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

STEIN FEDERAL

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA**Sec. 30, T-22S, R-25E**

12. COUNTY OR PARISH 13. STATE

Eddy**New Mexico**1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER **DRY HOLE**

2. NAME OF OPERATOR

MONSANTO COMPANY

3. ADDRESS OF OPERATOR

101 North Marienfeld, Midland, Texas 797014. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface**2210' FEL & 1980' FSL****MAR 7 1973**

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

**O. C. C.
ARTESIA, OFFICE****3869 DF**

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

x

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 8 3/4" hole to 10,436', logged & tested.**Verbal approval was received to plug and abandon as follows:****Sx. Cement****Depth**

35	10,270 - 10,170'
53	10,000 - 9,850'
35	8,070 - 7,970'
35	6,100 - 6,000'
35	4,100 - 4,000'
42	2,550 - 2,450'
20	55 - 0'

No casing will be pulled.**Hole between cement plugs will be filled w/ mud better than 25¢ Gal per Bbl. Water.****Dry hole marker will be set at surface w/ location marked thereon.**

18. I hereby certify that the foregoing is true and correct

SIGNED

A. W. Wood

TITLE

District Production Mgr.

DATE

March 1, 1973

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side

RECEIVED
MAR - 5 1973
 U. S. GEOLOGICAL SURVEY
 ARTESIA, NEW MEXICO

APPROVED
MAR 6 - 1973
[Signature]
 H. L. BECKMAN
 ACTING DISTRICT ENGINEER

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations; and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.