

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYN. M. & C. C. CORR
SUBMIT IN THE
(Other instruct
verse side)COPY to
Form Approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 0400877-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

JAN 6 1977

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Inexco Oil Company

O. C. C.
ARTESIA, OFFICE

3. ADDRESS OF OPERATOR

1100 Milam, Suite 1900, Houston, Texas 77002

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

Unit F, 1650' FNL & 1650' FWL of Sec. 30-21S-26E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

KB 3462', GL 3450'

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

USA - Boscowitz

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT

Catclaw Draw

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

30-21S-26E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed Procedure to P&A Well:

1. Set cement retainer at 10,558', 100' above top perforations, squeeze cement below retainer
2. Load well with 9.5 ppg mud.
3. Cut and recover 2200' 4½ casing, leaving no exposed sands below 2200'
4. Set 100' cement plug 2150' - 2250', 50' in and 50' out of 4½ casing
5. Set 20' cement plug in top of 8-5/8 surface. Weld on plate and install marker as per New Mexico State rules

RECEIVED

JUL - 2 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Marion Tebbbs

TITLE Production Engineer

DATE June 29, 1976

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side