

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TR. DATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC 066156

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☐ GAS WELL ☐ OTHER ☒ Active Drilling **RECEIVED**

2. NAME OF OPERATOR

Perry R. Bass

3. ADDRESS OF OPERATOR

P. O. Box 1178 Monahans, Texas 79756

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface 1980' FN & WL of Section 27 ARTEMA, OFFICE

7. UNIT AGREEMENT NAME

Big Eddy

8. FARM OR LEASE NAME

Big Eddy Unit

9. WELL NO.

35

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 27, T20S, R30E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3334 GR

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) Alter Casing Designs

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON* ☐

CHANGE PLANS ☐

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) ☐

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Salt Protection Casing:

No.	Description	Thds OFF	From	To
Jts.		Length		
--	Rotary correction	15	0	15
39	13 3/8" OD 48#/ft H-40 ST&C csg	1481	15	1496
12	13 3/8" OD 54.5#/ft K-55 ST&C csg	462	1496	1958
--	Float collar	2	1958	1960
1	13 3/8" OD 54.5#/ft K-55 ST&C csg	38	1960	1998
--	Float shoe	2	1998	2000

Intermediate Casing: See Reverse Side

Production Casing: See Reverse Side

18. I hereby certify that the foregoing is true and correct

SIGNED

Jack L. Simon

TITLE Division Engineer

DATE March 30, 1973

(This space for Federal or State office use)

APPROVED BY

John A. Knapp

TITLE DISTRICT ENGINEER

DATE APR 2 1973

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

U.S. GOVERNMENT PRINTING OFFICE: 1963-O-685229
867-831

Intermediate Casing:

No. Jts.	Description	Thds Off Length	From	To
--	Rotary correction	14	0	14
58	8 5/8" OD 24#/ft K-55 ST&C csg	2184	14	2198
--	Halliburton DV tool	2	2198	2200
--	BOT pin packer	6	2200	2206
5	8 5/8" OD 24#/ft K-55 ST&C csg	194	2206	2400
18	8 5/8" OD 28#/ft H-40 ST&C csg	700	2400	3100
22	8 5/8" OD 32#/ft H-40 ST&C csg	858	3100	3958
--	Float collar	2	3958	3960
1	8 5/8" OD 32#/ft H-40 ST&C csg	38	3960	3998
--	Float shoe	2	3998	4000

Production Casing:

No. Jts.	Description	Thds Off Length	From	To
--	Rotary correction	13	0	13
312	5 1/2" OD 17#/ft N-80 LT&C csg	12481	13	12494
3	5 1/2" OD 17#/ft S-95 LT&C csg	120	12494	12614
--	Float collar	2	12614	12616
1	5 1/2" OD 17#/ft S-95 LT&C csg	40	12616	12656
--	Float Collar	2	12656	12658
1	5 1/2" OD 17#/ft S-95 LT&C csg	40	12658	12698
--	Float shoe	2	12698	12700