

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR. DATE*
(Other instructions on re-
verse side)

NM0536388

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-05536388

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wigwam

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

31-21S-23E

12. COUNTY OR PARISH

Eddy

13. STATE

N.M.

1. OIL ☐ GAS ☒ OTHER ☐
WELL WELL

RECEIVED

2. NAME OF OPERATOR

Hanagan Petroleum Corporation

MAY 2 1973

3. ADDRESS OF OPERATOR

P.O. Box 1737, Roswell, New Mexico 88201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

ARTESIA, OFFICE

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4016' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

4/18/73: Spud 10:30 AM. Moranco contractor.

4/19/73: TD 150', 17½" hole, ran 7 jts. 13-3/8" 62# casing, set @ 150' w/125 sx. Class "C" + 2% CaCl. Plug down 1:45 AM. Cement circ. 1.32 slurry vol. cu. ft./sx, 7500 temp., slurry mixed, est. fm. temp. @ 7500, compressive strength 565#. Drlg. plug 1:45 PM 4/19/73. WOC 12 hrs. Press. up 600# for 30", no press. drop.

4/23/73: TD 1950', 12¼" & 11" hole, ran 58 jts. 8-5/8" 24# ST&C (1962'), set @ 1950', cemented w/750 sx. Class "C" 1/4# flocl, 5# gilsonite, 2% CaCl. + 150 sx. Class "C" 1/4# flocl, 2% CaCl. Plug down 11:00 AM, 4/23/73. Cement did not circ. Ran temp. survey, T/cement 800'. 1" tbgs., all Class "C" 4% CaCl - 1st batch - 25 sx., did not tag. 2nd batch - 30 sx., tag 592'. 3rd batch - 30 sx., tag 555'. 4th batch - 50 sx., tag 465' (P/70 bbls.mud, N.R.) 5th batch - 75 sx., tag 363'. 6th batch - 90 sx. cement circ. 7:15 AM (4/24/73). Total 1200 sx. WOC 48 hrs. 4/25/73. Drld. plug @ 11:00 AM 4/25/73. Press. up 1000#, 30" OK no press. drop.

RECEIVED

MAY - 4 1973

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

W. L. BEEKMAN

TITLE

Agent

DATE

5/2/73

(This space for Federal or State office use)

APPROVED BY

COPIATIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side